






	0-10 VDC DIMMING		ON/OFF MOMENTARY SWITCHES		
					
	NEW	NEW	Two Pushbutton, White Option	2 pushbutton white 4 pushbutton ivory 6 pushbutton ivory	TT-K3M TT-KE
Item #	TT-L4	TT-L6	TT-S Series	TT-G Series	TT-K Series
Description	0-10 VDC dimmer	0-10 VDC dimmer	Low Voltage Momentary Override Switch	Low Voltage Momentary Relay Switch	Low Voltage Momentary Key Switch
User Interface					
# of Push Buttons	4	6	1, 2, 4 or 6	2, 4 or 6	None, 1 Momentary on/off key switch
Push Buttons Operations	1M cycles	1M cycles	1M cycles	1M cycles	N/A
Tactile Feel On Push Button	Yes	Yes	Yes	Yes	N/A
Push Buttons LEDs	Yes	Yes	Yes, 1, 2 or 4	Yes, for ON pushbutton only	N/A
Finder LED	Yes	Yes	Yes	Yes	N/A
Input/Output					
Dimming Output	0-10 VDC can sink 20mA and/or source 10mA	0-10 VDC can sink 20mA and/or source 10mA	No	No	No
Power Requirement	24 VDC, 45mADC, can share sensor power pack	24 VDC, 45mADC, can share sensor power pack	N/A	N/A	N/A
Low Voltage Relay Output	Yes, for control of Power Pack	Yes, for control of Power Pack	Yes, to switch input on relay panel or controller	Yes, to switch input on relay panel or controller	Yes, to switch input on relay panel or controller
Power Pack Compatibility	Leviton OPP20-OD1, OSP20-ODO; Sensor Switch MP20/PP20; most 24 Vdc Power Packs	Leviton OPP20-OD1, OSP20-ODO; Sensor Switch MP20/PP20; most 24 Vdc Power Packs	N/A	N/A	N/A
Low Voltage Occupancy Sensor Input for Vacancy mode - (Manual On/Auto Off) and Auto On/Manual Off/Auto Off	Yes	Yes	N/A	N/A	N/A
Low Voltage Occupancy Sensor Compatibility	Leviton and Sensor Switch Low Voltage Sensors	Leviton and Sensor Switch Low Voltage Sensors	N/A	N/A	N/A
Relay Panel Switch Input Compatibility*	N/A	N/A	Cooper Controls LiteKeeper, Hubbell CX and LX, LC&D Bluebox, Acuity Brands Controls SwitchPak and Synergy	N/A	Cooper Controls LiteKeeper, Hubbell CX and LX, LC&D Bluebox, Acuity Brands Controls SwitchPak and Synergy
Lighting Relay Compatibility	N/A	N/A	N/A	General Electric RR7/RR9, Wattstopper HDR, ILC 2R7/2R9	N/A
Operation					
Manual Light Level Adjustment	Yes, Up and Down push button	Yes, Up and Down push button	N/A	N/A	N/A
Light Level Memory Push Button	No	Yes, 2 user defined	N/A	N/A	N/A
3-Way or More Way Support	Yes, requires twisted pair between each unit	Yes, requires twisted pair between each unit	N/A	N/A	N/A
Returns to last light level on power up	Yes	Yes	N/A	N/A	N/A
Settable Ramp Time	Yes, 3 second default	Yes, 3 second default	N/A	N/A	N/A
Settable Minimum and Maximum Vdc Output Range	Yes, 1-10 Vdc default	Yes, 1-10 Vdc default	N/A	N/A	N/A
General					
Decorator-Style	Yes	Yes	Yes	Yes	Yes
Color Options	White, Gray. Contact factory for other colors	White, Gray. Contact factory for other colors	White, Ivory, Gray. Contact factory for other colors	White, Ivory, Gray. Contact factory for other colors	White, Ivory, Gray. Contact factory for other colors
Removable Terminal Block	Yes	Yes	Yes	Yes	Yes
Warranty	5 year	5 year	5 year	5 year	5 year
Compliant with CEC Title 20 & 24	Yes	Yes	N/A	N/A	N/A